

Alternatives to systemd

This page describes the various init systems which are available as alternatives to systemd

Init is the first process started during system boot. It is a daemon process that continues running until the system is shut down. Init is the direct or indirect ancestor of all other processes, and automatically adopts all orphaned processes. It is started by the kernel using a hard-coded filename; if the kernel is unable to start it, panic will result. Init is typically assigned process identifier 1.

The init *scripts* (aka *rc* runtime configuration scripts) are launched by the init process to guarantee basic functionality on system start and shutdown. This includes (un)mounting of file systems and launching of daemons. A *service manager* takes this one step further by providing active control over launched processes, or [process supervision](#). An example is to monitor for crashes and restart processes accordingly.

These components combine to the init *system*. Some init systems incorporate the service manager in the init process or have init scripts in close relation to them. Below, such init systems are referred to as *integrated*, although entries in different categories may explicitly depend on each other.

A nice (but still non-comprehensive) overview of init systems can be found in [this](#) blog entry, titled “A history of modern init systems (1992-2015)”

init systems

| System | Description | Latest release |
|-------------------------------|---|----------------|
| BusyBox init | quite small init without runlevels, solely signal driven IPC (no fifos, sockets, SysV IPC) | 2019-10-25 |
| dinit | dependency based C++ init with process supervision, roll-back, and socket activation | 2020-01-01 |
| finit | fast, event based, modular, extensible (C hooks/plugins) init with SysV runlevels, proper daemon supervision and logging, and optional builtin getty and inetd | 2018-01-23 |
| nosh | exec chaining, dependency based daemontools family C++ init and supervision suite with reliable logging, (console) virtual terminal management, systemd unit file compatibility; can also be used as service manager under a different init | 2019-03-17 |
| openrc-init | init system of OpenRC , shipped since version 0.25 | 2019-08-20 |
| pies | dependency based GNU init daemon and super server with SysV runlevels, daemon supervision and logging, inetd functionality, socket activation, fine grained per service access control, understands SysV inittab, inetd.conf, and MeTA1 config files | 2019-07-02 |
| procd (2) | OpenWrt init and process/service management daemon with ubus integration | 2018-07-30 |
| runit-init | init from runit | 2014-08-10 |
| sinit | Simple init initially based on Rich Felker’s minimal init | 2018-03-26 |
| sninit | Small init implementation with SysV init like (sub)runlevels | 2017-12-29 |
| SysV init (2) | Traditional System V init. New release: v2.96 on July 07 2019 | 2019-09-11 |

| System | Description | Latest release |
|----------------------------------|---|----------------|
| ToyBox init (2) | similar to/(almost) compatible with BusyBox init (same config syntax/file) | 2019-10-28 |
| ToyBox oneit (2) | very simple init launcher (just (re)spawns a single child process and reacts to incoming signals) | 2019-10-28 |
| ueld | simple configuration, solely signal driven (like BSD and Busy/ToyBox init) | 2018-07-09 |
| uinit | Smallest init possible | 2017-05-16 |

process supervisors (overview) and service managers

service manager: a **suite of programs** which start and stop services, both long-running daemons and one-time initialization scripts, in the proper order according to a dependency tree

| Program | Description | Latest release |
|--|--|----------------|
| 66 | a collection of system tools built around s6 and s6-rc created to make the implementation and manipulation of service files easier | 2019-12-16 |
| Circus (docs) | runs, controls and monitors processes and sockets; written in Python ; uses ZeroMQ | 2019-12-27 |
| daemontools encore | an enhanced version of daemontools (github repository) | 2018-10-14 |
| GNU Shepherd | service manager and init daemon written in Guile (formerly known as GNU dmd) | 2019-05-11 |
| MiniBase | small userspace utilities for Linux; includes a process supervisor that can be used as stage 2 of process #1 via exec chaining akin to s6-svscan | 2019-11-14 |
| OpenRC (2, 3) | dependency based service management suite; includes a process supervisor and a simple init alternative | 2018-08-06 |
| perp | persistent process (service) supervisor and management framework for UNIX | 2013-01-11 |
| procer | process supervisor developed for mongrel2 | 2014-03-18 |
| restartd | a process-restarting daemon (aka Debian restartd) | 2013-01-11 |
| runit | process supervision suite in the line of daemontools; includes a simple init (2) replacement | 2014-08-10 |
| s6 | small process supervision suite for UNIX ala daemontools, runit, and perp; can be used as stage 2 of process #1 via exec chaining | 2019-10-21 |
| s6-rc | service management suite for s6 | 2018-08-20 |
| Supervisor | process control daemon written in Python | 2018-02-15 |
| ssm | simple service manager bash scripts for Linux | 2016-03-31 |
| supervise-daemon from OpenRC | superise-daemon introduced in OpenRC .0.21 | 2019-08-20 |
| Supervision Framework | OpenRC-like service management suite for daemontools(-encore), runit, and s6 | 2018-09-01 |
| systemctl-replacement | drop-in reading systemd service descriptions, with docker-oriented init function, written in Python | 2018-09-10 |

SysV init enhancement addons

| System | Description | Latest release |
|--------------------------|--|----------------|
| insserv | can be used with SysV -based init systems; provides dependency-driven system startup (dependencies are specified by LSB headers within init.d scripts) | 2012-11-14 |
| startpar | can be used by the SysV RC boot system executor to allow parallel process system startup | 2014-02-09 |

Safer, supervision-friendly replacements for crond and atd

| System | Description | Latest release |
|--|--|----------------|
| bcron | seperate tools for different tasks with strictly controlled communication between them; crontab compatible | 2015-08-12 |
| slicd (github) | modular design (seperate tools); crontab compatible | 2016-10-30 |
| uschedule | job scheduling suite that uses seperate tools for different tasks | 2004-08-?? |

udev alternatives for automatic Linux device file creation and management

[udev](#) (userspace /dev) is a device manager for the Linux kernel.

In April 2012, udev's source code was merged into the systemd source tree.[\[1\]](#)

Although udev can still be compiled for usage without systemd, Lennart Poettering said that they will not polish udevd outside of systemd[\[2\]](#), adding:

"Yes, udev on non-systemd systems is in our eyes a dead end, in case you haven't noticed it yet. I am looking forward to the day when we can drop that support entirely." So to be on the safe side, you probably want to use an alternative to udev:

| DevMan | Description | Last release |
|--|--|--------------|
| eudev (2, 3) | Gentoo's maintained fork of udev | 2017-11-22 |
| mdev | the plug-and-play manager built into BusyBox | 2018-07-31 |
| mdevd (github) | nonforking Linux kernel uevent handler daemon; uses the mdev config file format | 2018-08-14 |
| nldev (2) | Suckless netlink frontend for mdev; replacements for udevd and udevadm (see also nlmon) | 2018-08-03 |
| smdev | mostly mdev-compatible Suckless program to manage device nodes | 2015-04-12 |
| vdev (github) | portable UNIX userspace device-file manager | 2016-08-08 |

For more see [this](#) StackExchange question.

Related helper tool: [udevil](#) (2) (un)mounts removable devices without a password, shows device info, and monitors device changes. It can also mount ISO files, nfs://, smb://, ftp:, ssh:// and WebDAV URLs, and tmpfs/ramfs filesystems. Uses Glib and libudev (i. e. requires (e)udev) and can work completely without systemd, consolekit, policykit, dbus, udisks, gvfs & fuse (although it can coexist with any of these).

abandoned/defunct/discontinued/dormant/halted projects

Source code is available for download to anyone interested (in reviving them). Some of the projects listed below still compile/work while others may need some tweaking to make them work (again).

| Program | Description | Latest release |
|---|---|----------------|
| anopa | service management suite built around s6 ; can be used as init via exec chaining | 2017-06-20 |
| cinit (2, 3) | dependency based parallel init without subprocess output logging ala minit /daemontools | 2009-09-29 |
| daemond | daemon control and init daemon written in C++ (akin to dinit) | 2003-11-14 |
| depinit | supports parallel execution, dependencies, true roll-back, log pipelines, improved signaling, and unmounting of filesystems on shutdown | 2003-10-06 |
| einit (2, 3, 4) | modular, parallel, asynchronous, dependency based init system; XML (service) config files | 2007-12-18 |
| epoch | sequential, non-parallel init without dependency tracking designed for minimal footprint and unified configuration | 2015-06-23 |
| ettcl | custom Tcl-7.6 based interpreter to run the ETLinux init, crond, httpd, and telnetd daemons written in Tcl | 2002-??-?? |
| freedt | an independent daemontools reimplementation | 2014-09-03 |
| god (2) | an easily configurable, extensible, monitoring framework written in Ruby | 2014-03-06 |
| initng (2) | modular, extensible, parallel, asynchronous, dependency based init | 2007-03-25 |
| jinit | C++ init daemon supporting dependency tracking akin to the “ need ” concept | 2003-04-22 |
| minit | small dependency ordered, parallel init with proper subprocess supervision and logging | 2005-??-?? |
| Mudur + Comar | Python rc script (Mudur) and configuration/network/service manager with dbus integration (Comar) used in Pardus Linux | 2011-10-24 |
| myinit | parallel init with dependency tracking via reference counting (akin to the “ need ” concept) lacking proper supervision (respawn only, no output logging) | 2011-07-11 |
| ninit | dependency based parallel init with supervision, logging, and time-based scheduling akin to crond (HOWTO) | 2010-01-16 |
| pinit (sf) | XML configuration, dependency based fast parallel boot, modular design; uses Glib 2.0 and LibXML 2 | 2003-05-01 |
| serel (sf) | parallel service launcher with synchronisation and integrity-checking (primarily to speed up SysV init boots, akin to startpar) | 2002-08-06 |
| simpleinit (-msb) | dependency based (implements the “ need ” concept) sequential init without proper supervision (respawn only, no output logging); shipped with util-linux until v2.20; the msb fork is still used in Source Mage Linux | 2007-11-08 |
| System XVI | modular, self-healing, and interface-oriented service manager and init system | 2016-05-18 |
| twinit | tiny init largely written in x86 assembler | 2003-09-19 |
| upstart | “event based” init that reacts eagerly to incoming “events” to emulate dependency tracking; leaks memory | 2014-09-04 |
| uselessd (2) | forked from systemd v208 | 2015-01-06 |

See also

- [Gentoo wiki page: Comparison of init systems](#) ****Talk**** presents a more extensive / thorough “Detailed Feature Comparison Table”
- [Gentoo wiki page: Comparison of init systems](#)
- [A history of modern init systems \(1992-2015\)](#)
- [Understanding \(SysV\) init](#)
- [init systems overview](#)
- [init system features and benefits](#)
- [Demystifying the init system](#) (init written in [Ruby](#))
- Process supervision: Problem [apparently](#) solved
- How [process supervision](#) and [service management](#) differ (according to Laurent Bercot, author of [s6\(-rc\)](#))

Init-specific articles:

- [Upstart leaks memory](#) (reported on 2018-03-16, still no reaction whatsoever)
- Hints on how to build, install, configure, and use [ninit](#) as your default init
- [Hints](#) on how to replace your current init with [epoch](#) and [runit](#)
- [Gentoo wiki :: OpenRC](#)
- [guide: Using OpenRC on Arch Linux](#)
- [VoidLinux wiki :: Runit](#)
- [Obarun wiki :: s6-boot](#)
- [Replace systemd with busybox + minirc](#)
- [How to remove systemd from an Exherbo GNU/Linux installation](#)
- An [overview](#) of daemontools family supervision suites
- [Hints on how to perform socket activation with s6](#)
- [s6 init scheme \(2\)](#): Exec chaining into different “init stages”
- [runit init scheme \(2, 3\)](#): Process #1 starts (and supervises) 3 subprocesses implementing different “init stages”
- Simpler, more reliable, supervision-friendly alternatives to syslogd and klogd: [s6](#) + [s6-ipcservice](#) + [ucspilogd](#) + [s6-log](#) or [runit](#) + [socklog](#)

From:

<https://without-systemd.frama.wiki/> - **Without Systemd**

Permanent link:

https://without-systemd.frama.wiki/alternatives_to_systemd?rev=1579184113

Last update: **2020/01/16 15:15**

